

PRODUCT SHEET

REV 2.1 - EN202003



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM ISO 9001:2015 CERTIFIED by EuCI European Certification Institute LTD Certificate N:: GOTTEST201992

ORCANIZATION WITH FINVIRONMENTAL MANAGEMENT SYSTEM
ISO 14001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate No: GOTT223211001






SWINGING



H140 swing is specifically designed for wheelchair users. Once in, after blocking wheels with proper brakes, user must secure wheelchair with provided safety belts. It's mandatory to install this equipment into a dedicated area especially made for disabled users with a person in charge of steady control. It's also mandatory avoid able-bodied users accessing equipment, especially during closing time of playing area. That's to prevent improper use of equipment and its damage.

CATALOG COLLECTION DIMENSIONS (L x W x H) in cm MAXIMUM CFH IMPACT ATTENUATING SURFACE SUGGESTED AGE OF USE	117 min. 30,00 m ² - MAX 60,00 m ²
COMPOSITION	Aluminium 6005 alloy 90x90mm 2,5mm thick poles main structure with pyramidal polyurethane edge covers. Engraved 19mm thick HDPE sheet decoration panels. Basket built up with Ø40 and Ø60mm powder coated steel tubulars with aluminium treadplate 3+2mm thick sheet deck. Side entrance ramp with spring blocking system and HDPE sheet rounded edge. Ramp once blocked becomes a guardpanel. High-resistance safety belts are supplied anchored to basket deck. Basket jointed to frame by sphere bearings supports and an oil piston with speed limiter function. Equipped with 2 gripping ropes for swinging, both from frontal and side position.

SECURITY AREA



975

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.